

Transplus CVT

Transplus CVT is an automatic transmission fluid with a premium and innovative formulation, designed for use in Continuously Variable Transmissions (CVT), ensuring the reliable and smooth operation in CVT equipped vehicles even in low temperatures and challenging driving conditions. This product is not recommended for dual clutch transmissions. Proven performance in both chain- or pushbelt CVT applications. Available in the colors red (standard), yellow and green.

*Available in different colors

Properties

- + Extended service intervals
- + High oxidation stability
- + Enhanced transmission protection
- + Outstanding cold flow and cold starting properties
- + Smooth shifting at low outdoor temperatures and in tough conditions

Specifications

BMW/MINI: P/N 83 22 0 136 376, 83 22 0 429 154, EZL 799, EZL 799A, ZF V1, Punch CVT

Crysler/Dodge/Jeep: NS-2, CVTF +4, P/N 05191184AA

Chery: CVT, Fujiyuuko i-CVTF FG

Daihatsu: AMMIX CVTF DC, DFC, DFE, TC

Mercedes/Daimler: CVT 28/MB-Approval 236.20

Ford: CVT 23, CVT 30, M2C-199-A/933-A, Mercon C, Motocraft XT-7-QCFT, Spec. WSS-M2C933-A

GM/Saturn: DEX-CVT, CVTF I-Green2, P/N 22688912

Honda: HMMF, CVT Fluid, HCF-2, P/N 08200-9006

Hyundai/Kia/Mitsubishi: CVTF 1, J1, J4, ECO J4, J4+, SP-III (CVT), SP-CVT 1

Idemitsu: CVTS-EX1, MG EM-CVT

JASO: M358, M349, M348

Mazda: TFF CVT Fluid TC, JWS 3320

Nissan: KTF-1, CVTF NS-1, NS-2, NS-3, Matic W

Renault: Elf Matic CVT

Subaru: NS-2, CV-30, iCVT F/FG, ECVT, Lineartronic CVT, CVT II K0425Y0711, Lineartronic High Torque K0421Y0700

Suzuki: CVTF TC, 3320, 4401, NS-2, Green 1/1V, Green 2, S-CVT

Toyota: TC, CVT Fluid FE

Volvo: CVT 4959

Volkswagen/Audi: G 052 180 (-A2), G 052 516 Multitronic




Table of properties

Property	Test Method	Unit	Value
Density 15°C	DIN 51757	kg/m ³	845
Kinematic Viscosity @ 40°C	ASTM D 7042	mm ² /s	33
Kinematic Viscosity @ 100°C	ASTM D 7042	mm ² /s	7.2
Viscosity Index	DIN ISO 2909		185
Viscosity @ -40°C (Brookfield)	ASTM D 2983-09	mPas	≤ 20000
Pour Point °C	ASTM D 7346	°C	max. -45
Flash Point °C	DIN ISO 2592	°C	min. 200
Color/Appearance			Red/Rot Yellow/Gelb Green/Grün

** Characteristic values can fluctuate within the normal range. The information in this publication is based on our current knowledge and experience. They do not release the user from their own tests and trials due to possible influences during the processing and application of our products. A legally binding assurance of certain properties or the suitability for a specific application cannot be derived from our information. It is the responsibility of the recipient of our products to observe any property rights as well as existing laws and regulations.*

