



Bodro OW-40

The innovative formulation of Bodro 0W-40 enhances the wear performance and maximizes engine performance. The optimal cold starting properties allow excellent low temperature performance and increased fuel economy. Ideal for gasoline engines.



Properties

- + Excellent low temperature performance
- + Excellent fuel economy performance
- + Improved cold start properties
- + Excellent wear performance technology

Specifications

API SN ACEA A3/B4 Porsche A40 GM / Ford 937-A Renault RN 0700/0710 MB 229.3/229.5 VW 502 00/505 00

Table of properties

Property	Test Method	Unit	Value
Density 15°C	ASTM D 4052	Kg/m³	865.8
Kinematic Viscosity @ 40°C	ASTM D 445	cSt	106.00
Kinematic Viscosity @ 100°C	ASTM D 445	cSt	14.27
Viscosity Index	ASTM D 2270		137
Pour Point °C	ASTM D 97		-45
Flash Point °C	ASTM D 97		241

^{*} Characteristic values can fluctuate within the normal range. The information in this publication is based on our current knowledge and experience. They do not release the user from their own tests and trials due to possible influences during the processing and application of our products. A legally binding assurance of certain properties or the suitability for a specific application cannot be derived from our information. It is the responsibility of the recipient of our products to observe any property rights as well as existing laws and regulations.

