Germany

Bodro 5W-20

This premium high quality oil consists of fully synthetic base oils and the latest additive technology, which are specifically designed to increase fuel- as well as exhaust efficiency while maintaining premium level engine protection properties and delivering optimal performance. High shear- and oxidation stability prevent wear and tear as well as gelling and viscosity increase.



Properties

- + Excellent fuel economy performance
- + Protection from deposit-/sludge formation
- + Outstanding oxidation- and temperature stability
- + Advanced wear protection and cleanliness
- + Excellent retained low temperature properties

Specifications

API SN-RC/CF ILSAC GF-5 ACEA C5 GM / Ford 948-A/948-B

Table of properties

Property	Test Method	Unit	Value
Density 15°C	ASTM D 4052	Kg/m³	865.8
Kinematic Viscosity @ 40°C	ASTM D 445	cSt	106.00
Kinematic Viscosity @ 100°C	ASTM D 445	cSt	14.27
Viscosity Index	ASTM D 2270		137
Pour Point °C	ASTM D 97		-45
Flash Point °C	ASTM D 97		241

^{*} Characteristic values can fluctuate within the normal range. The information in this publication is based on our current knowledge and experience. They do not release the user from their own tests and trials due to possible influences during the processing and application of our products. A legally binding assurance of certain properties or the suitability for a specific application cannot be derived from our information. It is the responsibility of the recipient of our products to observe any property rights as well as existing laws and regulations.

