

Cruiser 10W-40

Formulated for the performance of 4T motorcycles even in severe operating conditions. The extreme pressure additives guarantee gear protection throughout the year whilst extending engine life and providing excellent shear stability. Suitable for street & road bikes, trails and off-road bikes.



Properties

- + Excellent wear protection
- + High temperature protection
- + Outstanding wet clutch protection for maximum power transfer and smooth shifting
- + Anti-oxidation additives reduce oil viscosity breakdown to prevent engine clogging
- + Anti-friction to reduce abrasions within the engine
- + Excellent shear stability

Specifications

API SL
JASO MA

Table of properties

Property	Test Method	Unit	Value
Density 20°C	ASTM D 1298	Kg/L	0.864
Kinematic Viscosity @ 40°C	ASTM D 445	mm ² /s	102.1
Kinematic Viscosity @ 100°C	ASTM D 445	mm ² /s	14.6
Viscosity Index	ASTM D 2270		150
Viscosity at -30°C (CCS)		mPas	≤ 6600
TBN	ASTM D 2896	mg KOH/g	7.1
Pour Point °C	ASTM D 97		-35
Flash Point °C	ASTM D 92		232

* Characteristic values can fluctuate within the normal range. The information in this publication is based on our current knowledge and experience. They do not release the user from their own tests and trials due to possible influences during the processing and application of our products. A legally binding assurance of certain properties or the suitability for a specific application cannot be derived from our information. It is the responsibility of the recipient of our products to observe any property rights as well as existing laws and regulations.

