

Germany

LUBPLUS GmbH | Radlkoferstr. 2 | 81373 München | Germany

Diesel Winter Care

Lubplus Diesel Winter Care ensures improved flow properties of all diesel fuels and is suitable for use in all diesel aggregates with or without diesel particulate filter. Winter safe down to -28 °C (depending on the fuel quality). Reliably prevents from formation of paraffin crystals at low temperatures. Also suitable for stationary diesel.



Properties

- Prevents the formation of paraffin crystals when used in a timely manner.
- + Easy application. Product works during operation.
- + Optimal flow properties of the diesel fuel ensure optimal operation of all system components and safe driving conditions in winter periods.
- + Maintains the flow properties of the fuel and improves filterability of the diesel fuel and prevents from blocking of the fuel filter.
- + Improved cold start properties in winter.

Application

- + Add to the tank before refueling regularly before frosty winter periods.
- + Dosage 1:1000 (150 ml are sufficient for 150 liters of diesel fuel).
- + If diesel already has paraffin crystals, the entire vehicle must be warmed up for several hours above freezing.
- + Attention: Product for preventative application! Store frost free! Shake before use! Do not overdose!

Table of properties

Property	Test Method	Unit	Value
Density Flash Point °C	ASTM D 7042 ASTM D 92	g/cm³ °C	0.89 > 64
Color/Appearance			Colourless liquid

^{*} Characteristic values can fluctuate within the normal range. The information in this publication is based on our current knowledge and experience. They do not release the user from their own tests and trials due to possible influences during the processing and application of our products. A legally binding assurance of certain properties or the suitability for a specific application cannot be derived from our information. It is the responsibility of the recipient of our products to observe any property rights as well as existing laws and regulations.